

Recommended P.C.B Layout(Top Side)


| PART NO.  | Dimensions |       |
|-----------|------------|-------|
|           | A          | B     |
| 1*2P      | 2.00       | 6.00  |
| 1*3P      | 4.00       | 8.00  |
| 1*4P      | 6.00       | 10.00 |
| 1*5P      | 8.00       | 12.00 |
| 1*6P      | 10.00      | 14.00 |
| 1*7P      | 12.00      | 16.00 |
| 1*7P      | 14.00      | 18.00 |
| 1*8P      | 16.00      | 20.00 |
| 1*9P      | 18.00      | 22.00 |
| PH2.0-11A | 20.00      | 24.00 |
| PH2.0-12A | 22.00      | 26.00 |
| PH2.0-13A | 24.00      | 28.00 |
| PH2.0-14A | 26.00      | 30.00 |
| PH2.0-15A | 28.00      | 32.00 |
| PH2.0-16A | 30.00      | 34.00 |

EST2001 W V - 1\*NP X - X - X X - NK-HF

非通代码-PIN: W V - 1\*NP X - X - X X - NK-HF  
 PIN数: A本色 B带扣 C超厚 D颜色 E颜色 F颜色 G颜色 H颜色  
 1单排 2双排  
 F为PIN针镀层 S为PIN针镀锡  
 NK为NO MARK MK为MARK  
 P为PDS, 2为PBT, 3为LCP, 4为ABS, 5为PBT, 6为PBAE  
 1为打眼 2为平号 3为尖型 2为悬有柱 L0为定位  
 V: 示意180°直针, VS立式  
 R: 示意90°弯针, BS立式  
 W: 后带2示意V2  
 \*示意针座  
 W后无数字以材质为W  
 W后带2示意V2

NOTES:  
 MATERIAL: PA66UL94V-0  
 CONTACT: BRASS, TIN PLATED  
 CURRENT RATING: 2A AC/DC  
 VOLTAGE RATING: 100V AC/DC  
 TEMPERATURE RANGE: -25°C~+85°C  
 CONTACT RESISTANCE: 20mΩ MAX  
 INSULATION RESISTANCE: 1000MΩ MIN  
 WITHSTANDING VOLTAGE: 800V AC/MINUTE  
 FLASH: 0.05MAX; WARPAGE: 0.08MAX

| 日期版次<br>REVISION | 日期<br>DATE | 变更内容<br>DESCRIPTION | 核 准<br>APPROVAL BY |
|------------------|------------|---------------------|--------------------|
|                  |            |                     |                    |
|                  |            |                     |                    |
|                  |            |                     |                    |



**东莞市羿通实业有限公司**  
**DONGGUAN EASTOM ELECTRONIC Co., Ltd.**

|                                  |         |                           |             |
|----------------------------------|---------|---------------------------|-------------|
| 料号PART NO: EST2001WR-1*NPX-L0    |         | 一般公差<br>GENERAL TOLERANCE |             |
| 品名 TITLE: PH2.0-wafer 90°(带定位打K) |         | X. X ±0.15                |             |
| 材料: PA66UL94V-0                  | 单位: MM  | 包装规格: 1K/包                | X. XX ±0.10 |
| 制图: LI                           | 审核: LI  | 核准: LI                    | X. XX ±0.05 |
| 日期: 2022/05/11                   | 比例: 1:1 |                           | ANGLE ±1°   |

