



a-a SECTION



c-c SECTION



b-b SECTION

EST2002 T P X - 2 X - G

↑ 羿通代码+间距	↑ T示端子	↑ X普通脚 H高脚	↑ X普通 L长 S短	↑ X公端 G母端 C示意90° S示意180°
	P磷铜 B黄铜 E合金铜		0素材 2镀锡先冲后镀 3镀锡先镀后冲	5G、15G示意镀金5U"或15U", 1G示意镀金1U"

SPECIFICATIONS

- Applicable wire:AWG#24~#28
- Voltage rating: 250V DC/AC (rms)
- Current rating:2.5-1.0A
- Withstand voltage: 800V AC(rms)
- Working Temperature:-25°C+85°C
- Insulation resistance:≥1000MΩ
- Contact resistance:≤0.02Ω

A1			husongxing
版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2002TPX-2X-G		一般公差 GENERAL TOLERANCE	
品名 TITLE: PHD2.0-T		X.X ±0.30	
材料: C5191	单位: MM	包装规格: 10K/卷	比例: 1:1
制图:	审核:	核准:	日期: 2022/05/21

