



■ SPECIFICATIONS

- Voltage rating: 125V AC/DC
- Current rating: 1A AC/DC
- Withstanding Voltage: 500V AC/minute
- Insulation resistance: 1000MΩ Min.
- Temperature range: -20°C - +85°C
- Contact resistance: 20mΩ Max.

■ HOUSING

- Part No.:
- Poles: 2-15
- Material: Nylon66 UL 94V-0
- Q'TY: 1000 Pcs/Bag

EST2003 H - 1*NP X - B - X - HF-NK - X

- ↑ 羿通代码+间距
- ↑ H 示意胶壳, H后无数字默认材质V0, H后带数字2示意材质V2
- ↑ 1*NP 示意单排, 2示意双排
- ↑ X 本色, B 黑色, R 红色, L 蓝色, Y 黄色, G 绿色, C 透明
- ↑ X 普通, B 带扣, C 刺破, 2L 示意两侧带锁扣, U 超薄F防呆型, HF 带高凸点, LC 带低凸点, E 有耳
- ↑ X 公胶壳, G 母胶壳
- ↑ NO MARK
- ↑ HF 示意无卤, NF 普通含卤
- ↑ A 灼热丝750, B 灼热丝850, X 普通料



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2003H-1*NPX-X

品名 TITLE: MX2.0-H

材料: PA66

单位: MM

包装规格:

比例: 1:1

制图:

审核:

核准:

日期: 2022/5/31

一般公差
GENERAL TOLERANCE
X.X ± 0.25
X.XX ± 0.20
ANGLE ± 1°

