



| PART NO | dimensions | |
|---------|------------|-------|
| | A | B |
| 2P | 6.64 | 4.60 |
| 3P | 8.64 | 6.60 |
| 4P | 10.64 | 8.60 |
| 5P | 12.64 | 10.60 |
| 6P | 14.64 | 12.60 |
| 7P | 16.64 | 14.60 |
| 8P | 18.64 | 16.60 |
| 9P | 20.64 | 18.60 |

EST2008 H - 1*NP X - X - X - HF-NK - X

↑ 贯通代码+间距 ↑ H示意胶壳, H后无数字默认材质V0, H后带数字2示意材质V2

↑ 1*NP ↑ PIN数
1示意单排
2示意双排

↑ X ↑ X本色
↑ B ↑ B黑色
↑ R ↑ R红色
↑ L ↑ L蓝色
↑ Y ↑ Y黄色
↑ G ↑ G绿色
↑ C ↑ C透明

↑ X - X - X ↑ X普通
 ↑ B带扣
 ↑ C刺破
 ↑ 2L示意两侧带锁扣
 ↑ U超薄P架架型
 ↑ HV带高凸点
 ↑ LC带低凸点
 ↑ X卡槽
 ↑ E有耳

↑ X - X ↑ X公胶壳
 ↑ G母胶壳

↑ HF-NK ↑ NO MARK
 ↑ HF示意无齿
 ↑ NP普通含齿

↑ X ↑ A灼热丝750
 ↑ B灼热丝850
 ↑ X普通料

SPECIFICATIONS

- Voltage rating:125V AC/DC;
- Current rating:2A AC/DC;
- Withstanding Voltage:800V AC/minute
- Insulation resistance:800MΩ Min
- Temperature range:-25°C~+105°C
- Contact resistance:20mΩ Max



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

| | | | | |
|------------------|--------------------------|---------------------|-------------------|---------------------------|
| 料号PART NO: | EST2008H-1*NPX-X-NK-HF-X | | | 一般公差 GENERAL TOLERANCE |
| 品名 TITLE: | 51005-H(公) | | | X.X ±0.35 |
| 材料: PA66 | 单位: MM | 包装规格: 10K/包 | 比例: 1:1 | X.XX ±0.20 |
| 日期版次 REVISION | 日期 DATE | 变更内容 DESCRIPTION | 核准 APPROVALBY | ANGLE ±1° |
| 制图: | 审核: | 核准: | 日期: 2021/06/14 | |