

EST2009 T P X - 2 X - G

↑ 羿通代码+间距 ↑ T 示意端子 ↑ X 普通脚 ↑ H 高脚 ↑ E 增高型脚

↑ X 普通 ↑ L 长 ↑ S 短 ↑ X 公端 ↑ G 母端 ↑ C 示意90° ↑ S 示意180°


0 素材
 2 镀锡先冲后镀
 3 镀锡先镀后冲
 5G、15G 示意镀金5U' 或15U'
 1G 示意镀金1U'

P 磷铜
 B 黄铜
 E 合金铜

SPECIFICATIONS

- Applicable wire:
- Voltage rating: 250V DC/AC (rms)
- Current rating: 2.5A
- Withstand voltage: 800V AC(rms)
- Working Temperature: -25℃+85℃
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤0.02Ω

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY



东莞市羿通实业有限公司

DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2009TPX-2X-G			一般公差 GENERAL TOLERANCE	
品名 TITLE: 51006-T			X.X ±0.30	X.XX ±0.20
材料: C5191	单位: MM	包装规格:	比例: 1:1	ANGLE ±1°
制图:	审核:	核准:	日期: 2022/07/11	