




DETAIL F
SCALE 2:1



SECTION A--A



SECTION B--B



SECTION C--C

EST2011 T P X - 2 X- G

↑ 羿通代码+间距
↑ T示意端子
↑ X普通脚
↑ H高脚
↑ EH增高型脚
↑ X普通
↑ L长
↑ S短
↑ X公端
↑ G母端
↑ C示意90°
↑ S示意180°

0素材
2镀锡先冲后镀
3镀锡先镀后冲
5G、15G示意镀金5U"或15U"
1G示意镀金1U"

P磷铜
B黄铜
E合金铜

Technical parameters

- (1) Rated Voltage: 250V DC/AC (RMS)
- (2) Rated Current: 3A AC/DC
- (3) Withstanding voltage: 1000V AC/Minute
- (4) Working Temperature: -25° to +85°
- (5) Plating specification: Sn60u' Ni15u'



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号 PART NO: EST2011TPX-2X-G

品名 TITLE: PHB-T

材料: C5191

单位: MM

包装规格:

比例: 1:1

制图:

审核:

核准:

日期: 2022. 6. 18

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVAL BY

一般公差 GENERAL TOLERANCE	
X. X	±0.30
X. XX	±0.20
ANGLE	±1°

