



Circuit	Dimension(mm)					
	A	B	C	D	E	
2*2	2.00	6.60	4.60	3.10	3.00	
2*3	4.00	8.60	6.60	3.10	3.00	
2*4	6.00	10.60	8.60	4.80	2.60	
2*5	8.00	12.80	10.60	小扣	4.80	2.30
				大扣	7.50	5.00
2*6	10.00	14.80	12.60	8.20	5.80	
2*7	12.00	16.80	14.60	9.70	7.20	
2*8	14.00	18.80	16.60	小扣	9.70	7.20
				大扣	12.30	9.70
2*9	16.00	20.80	18.60	小扣	12.30	9.70
				大扣	14.10	11.40
2*10	18.00	22.80	20.60	12.30	9.70	
2*11	20.00	24.80	22.60	12.30	9.70	
2*12	22.00	26.80	24.60	16.25	13.65	
2*13	24.00	28.80	26.60	16.25	13.65	
2*14	26.00	30.80	28.60	16.25	13.65	
2*15	28.00	32.80	30.60	16.25	13.65	
2*16	30.00	34.80	32.60	16.25	13.65	
2*17	32.00	36.80	34.60	16.25	13.65	
2*18	34.00	38.80	36.60	16.25	13.65	
2*20	38.00	42.80	40.60	16.25	13.65	

EST2011 H - 1*NP X - B - NK - HF-X

↑ 羿通代码+间距 ↑ H 示意胶壳, H后无数字默认材质V0, H后带数字2示意材质V2

↑ 1示意单排, 2示意双排

↑ PIN数

X 本色
B 黑色
R 红色
L 蓝色
Y 黄色
G 绿色

X 普通
B 带扣
C 刺破
L 示意LOCK TYPE
U 超薄防呆型
HV 带高凸点
LC 带低凸点,
K 卡槽
E 有耳
NE 无耳

NO MARK

HF 示意无卤
NF 普通含卤

X 公胶壳
G 母胶壳

Technical parameters

- (1) Applicable wire: AWG#18-#22
- (2) Rated Voltage: 250V DC/AC (RMS)
- (3) Rated Current: 3A AC, DC
- (4) Withstanding voltage: 1500V AC/Minute
- (5) Working Temperature: -25° to +85°

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVAL BY



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号 PART NO: EST2011H-2*NPX-B-X			
品名 TITLE: PHB-H(带扣)			
材料: PA66	单位: MM	包装规格:	比例: 1:1
制图:	审核:	核准:	日期: 2022. 6. 18

一般公差 GENERAL TOLERANCE
X, X ±0.25
X, XX ±0.20
ANGLE ±1°

