



A-A SECTION



B-B SECTION

0.85 ± 0.08



C-C SECTION

技术参数: SPECIFICATIONS

适用线规: AWG#22~#28

Applicable wire: AWG#22~#28

额定电压: 250V DC/AC (有效值)

Voltage rating: 250V DC/AC (rms)

额定电流: 2.5-1.0A

Current rating: 2.5-1.0A

耐压值: 800V AC(有效值)

Withstand voltage: 800V AC(rms)

工作温度: -25℃~+85℃

Working Temperature: -25℃+85℃

绝缘电阻: ≥1000MΩ

Insulation resistance: ≥1000MΩ

接触电阻: ≤0.02Ω

Contact resistance: ≤0.02Ω

EST2013 T P X - 2 X - X

↑ 羿通代码+间距

↑ T示意端子

↑ X普通脚
H高脚
E增高型脚

↑ X普通
L长
S短
U超薄

↑ X公端
G母端
C示意90°
S示意180°

P磷铜
B黄铜
E合金铜

0素材
2镀锡先冲后镀
3镀锡先镀后冲
4镀全镍(镀后冲)
4.2镀全银先冲后镀
5G、15G示意镀金5U或15U, 1G示意镀金1U



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2013TPX-2X-G

品名 TITLE: 51354-T

材料: C5191

单位: MM

包装规格: 10k/卷

比例: 1:1

制图:

审核:

核准:

日期: 2022/6/19

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

一般公差 GENERAL TOLERANCE	
X. X	±0.15
X. XX	±0.10
X. XXX	±0.05
ANGLE	±1°

