



EST2013 H - 1*NP X - B - X - HF-NK - X

↑
羿通代码+间距

↑
PIN数
1示意单排
2示意双排

↑
X 公散壳
G 母散壳

↑
NO MARK

X 本色
B 黑色
R 红色
L 蓝色
Y 黄色
G 绿色
C 透明

X 普通
B 带扣
C 明胶
2L 示意两侧带锁扣
U 超薄F 防呆型
HV 带高凸点
LC 带低凸点
K 带耳
E 有耳

↑
A 灼热丝750
B 灼热丝850
X 普通料

↑
HF 示意无齿
NF 普通含齿

H 示意散壳
H 后无数字默认材质V0
H 后带数字2示意材质V2

PIN数	A	B	C	D	E
2*4	11.20	6.00	9.40	4.50	4.70
2*5	13.20	8.00	11.40	6.50	4.70
2*6	15.20	10.00	13.40	8.50	7.80
2*7	17.20	12.00	15.40	10.50	7.80
2*8	19.20	14.00	17.40	12.50	7.80
2*9	21.20	16.00	19.40	14.50	7.80
2*10	23.20	18.00	21.40	16.50	7.80
2*11	25.20	20.00	23.40	18.50	7.80
2*12	27.20	22.00	25.40	20.50	7.80
2*13	29.20	24.00	27.40	22.50	7.80
2*14	31.20	26.00	29.40	24.50	7.80
2*15	33.20	28.00	31.40	26.50	7.80
2*16	35.20	30.00	33.40	28.50	7.80
2*17	37.20	32.00	35.40	30.50	7.80
2*18	39.20	34.00	37.40	32.50	7.80
2*19	41.20	36.00	39.40	34.50	7.80
2*20	43.20	38.00	41.40	36.50	7.80

SPECIFICATIONS

Applicable wire:
Voltage rating: 250V DC/AC (rms)
Current rating: 2.5-1.0A
Withstand voltage: 800V AC(rms)
Working Temperature: -25°C+85°C
Insulation resistance: ≥1000MΩ
Contact resistance: ≤0.02Ω

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2013H-2*NPX-B-X

品名 TITLE: 51354-H

材料: PA66	单位: MM	包装规格: 1K/包	比例: 1:1
制图: LI	审核: LI	核准: LI	日期: 2022/6/19

一般公差
GENERAL TOLERANCE
X.X ±0.30
X.XX ±0.20
X.XXX ±0.10
ANGLE ±1°

