



Poles	A	B	C	D
1*2P	7.30	2.50	3.50	5.70
1*3P	9.80	5.00	6.00	8.20
1*4P	12.30	7.50	8.50	10.70
1*5P	14.80	10.00	11.00	13.20
1*6P	17.30	12.50	13.50	15.70
1*7P	19.80	15.00	16.00	18.20
1*8P	22.30	17.50	18.50	20.70
1*9P	24.80	20.00	21.00	23.20
1*10P	27.30	22.50	23.50	25.70
1*11P	29.80	25.00	26.00	28.20
1*12P	32.30	27.50	28.50	30.70
1*13P	34.80	30.00	31.00	33.20
1*14P	37.30	32.50	33.50	35.70
1*15P	39.80	35.00	36.00	38.20
1*16P	42.30	37.50	38.50	40.70

EST2501 H - 1\*NP X - B - X - HF-NK - X

↑ 羿通代码+间距

↑ PIN数  
1示意单排  
2示意双排

↑ X 普通  
X 本色  
B 黑色  
R 红色  
L 蓝色  
Y 黄色  
G 绿色  
C 透明

↑ B 带扣  
C 刺破  
2L 示意两侧带锁扣

↑ X 公胶壳  
G 母胶壳

↑ NO MARK

↑ HF 示意无齿  
NF 普通含齿

↑ A 灼热丝750  
B 灼热丝850  
X 普通料

H示意胶壳,  
H后无数字默认材质V0  
H后带数字2示意材质V2

■ SPECIFICATIONS

- Voltage rating:250V AC/DC;
- Current rating:3A AC/DC;
- Withstanding Voltage:1000V AC/minute
- Insulation resistance:1000MΩ Min
- Temperature range:-25℃~+85℃
- Contact resistance:20mΩ Max



东莞市羿通实业有限公司  
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2501H-1\*NPX-X-X

品名 TITLE: XH2.5-H

Material: Nylon 66.UL94V-0 Unit: MM Q'ty/bao: 1000pcs Scale: 1:1

DR: CHKD: APPD: DATE: 2022/06/30

GENERAL TOLERANCE  
X.X ±0.30  
X.XX ±0.20  
ANGLE ±1°

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

