



EST2502 T B X - 2 X - S

↑ 羿通代码+间距
↑ T示意端子
↑ X普通脚
↑ H高脚
↑ P磷铜
↑ B黄铜
↑ E合金铜

X公端
G母端
X普通 C示意90°
L长 S示意180°
0素材
2镀锡先冲后镀
3镀锡先镀后冲
5G、15G示意镀金5U"或15U", 1G示意镀金1U"

■ SPECIFICATIONS

- Voltage rating:250V AC/DC;
- Current rating:2.5A AC/DC;
- Withstanding Voltage:800V AC/minute
- Insulatin resistance:1000MΩ Min
- Temperature range:-25℃~+85℃
- Contact resistance:20mΩ Max
- Applicable wire:#24~#28



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2502TBX-2X-S

品名 TITLE: SCN180° -T

材料: C2680

单位: MM

包装规格: 10K/卷

比例: 1:1

日期版次
REVISION

日期
DATE

变更内容
DESCRIPTION

核 准
APPROVALBY

制图:
李 建

审核:
余 刚

核准:
李海平

日期:
2022/7/2

一般公差 GENERAL TOLERANCE	
X. X	±0.30
X. XX	±0.20
X. XXX	±0.08
ANGLE	±1°

