



A-A SECTION



B-B SECTION



C-C SECTION

EST2502 T P X - 2 X - X

↑
羿通代码+间距

↑
T示意端子

↑
X普通脚
H高脚
E增高型脚

↑
0素材
2镀锡先冲后镀
3镀锡先镀后冲
5G、15G示意镀金5U"或15U"
1G示意镀金1U"

↑
P磷铜
B黄铜
E合金铜

↑
X公端
G母端
X普通
C示意90°
L长
S示意180°

■ SPECIFICATIONS

- Voltage rating: 250V AC/DC;
- Current rating: 2.5A AC/DC;
- Withstanding Voltage: 800V AC/minute
- Insulation resistance: 1000MΩ Min
- Temperature range: -25°C ~ +85°C
- Contact resistance: 20mΩ Max
- Applicable wire: #24~#28



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2502TPX-2X-X

品名 TITLE: SCN180-T(公)

材料:

单位: MM

包装规格:

比例: 1:1

制图:

审核:

核准:

日期: 2022/7/2

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

EST

一般公差
GENERAL TOLERANCE
X.X ±0.25
X.XX ±0.20
ANGLE ±1°

