



防呆型

EST2502 H - 1*NP X - X - X - HF-NK - X

↑ 羿通代码+间距 ↑ PIN数 ↑ X本色 ↑ X普通 ↑ X公胶壳 ↑ NO MARK ↑ A灼热丝750

↑ 1示意单排 ↑ 2示意双排 ↑ B黑色 ↑ C刺破 ↑ G母胶壳 ↑ 2L示意两侧带锁扣 ↑ B灼热丝850

↑ U超薄防呆型 ↑ HV带高凸点 ↑ HF示意无卤 ↑ NF普通含卤 ↑ X普通料

↑ Y黄色 ↑ LC带低凸点 ↑ K卡槽 ↑ E有耳

H示意胶壳, H后无数字默认材质V0, H后带数字2示意材质V2

- SPECIFICATIONS**
- Voltage rating: 250V AC/DC;
 - Current rating: 2.5A AC/DC;
 - Withstanding Voltage: 800V AC/minute
 - Insulation resistance: 1000MΩ Min
 - Temperature range: -25°C ~ +85°C
 - Contact resistance: 20mΩ Max

东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2502H-1*2PX-F				一般公差 GENERAL TOLERANCE	
品名 TITLE: SCN180°-H(防呆型)				X.X ±0.20	X.XX ±0.10 X.XXX ±0.05 ANGLE ±5°
材料: PA66	单位: MM	包装规格: 1K/包	比例: 1:1		
日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY	制图: 审核:	
				核准: 日期: 2020/7/2	