





EST1005 T P X - 2 X- X

↑ 羿通代码+间距
T示意端子
X公端
G母端
X普通 C示意90°
L长 S示意180°
0素材
2镀锡先冲后镀
3镀锡先镀后冲
5G、15G示意镀金5U"或15U", 1G示意镀金1U"
X普通脚
H高脚
P磷铜
B黄铜
E合金铜

- Notes:
1. Material: Phosphor bronze, T=0.12;
 2. Finish: Nickel 20U" min Over all.
Tin 80U" minn over nickel.
 3. Applicable Wire range: AWG#28~#32
 4. Insulation O. D. : 0.8mm (Max);
 5. Current Rating: 1A AC, DC;
 6. Vovtage RATING: 50V AC/DC;
 7. Temperature rang: -25°C~+85°C;
 8. Contact resistance: 20 MΩ Max;
 9. Insulation Resistance: 100 mΩ Min;
 10. Withstanding voltage: 500V AC/minute;
 11. Packin Qty: 2000PCS/Reel;



		东莞市羿通实业有限公司 DONGGUAN EASTOM ELECTRONIC Co., Ltd.		料号PART NO: EST1005TPX-2X-G		一般公差 GENERAL TOLERANCE	
				品名 TITLE: NH1.0-T		X.X ±0.25 X.XX ±0.20 ANGLE ±1°	
材料: C5191	单位: MM	包装规格:	比例: 1:1	日期: 2021.3.9			
日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY	制图:	审核:		

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

A
XR