



EST2509 T P X - 2 X- X

↑ 羿通代码+间距
↑ T示意端子
↑ X普通脚
↑ H高脚
↑ E增高型脚
↑ X公端
↑ G母端
↑ C示意90°
↑ S示意180°

0 素材
2 镀锡先冲后镀
3 镀锡先镀后冲
4 镀全镍(镀后冲)
5 镀全镍先冲后镀
5G、15G 示意镀金5U"或15U", 1G 示意镀金1U"

P 磷铜
B 黄铜
E 合金铜

PRODUCT SPECIFICATON

1. Material: BRONZE
2. Temperature range: -25°C ~ 85°C
3. Current rating: 2A AC/DC
4. Contact resistance: 10mΩ MAX
5. Insulation resistance: 1000MΩ MIN
6. Withstand voltage: 1000V AC/Minute
7. Applicable wire: AWG #28 TO #22

EST 东莞市羿通实业有限公司
DGEASTOM DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号 PART NO: EST2509TPX-2X-G

品名 TITLE: 5240-T母

材料: BRONZE 单位: MM 包装规格: 7K/ROLL 比例: 1:1

日期: 2022/7/3

一般公差 GENERAL TOLERANCE
<10 ±0.20
10~30 ±0.25
ANGLE ±1°

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

