



EST2504 T B X - 2 X - X

↑ 羿通代码+间距    ↑ T示端子    ↑ P磷铜    ↑ B黄铜    ↑ E合金铜    ↑ X普通脚    ↑ H高脚    ↑ E增高型脚    ↑ 0素材    ↑ 2镀锡先冲后镀    ↑ 3镀锡先镀后冲    ↑ 4镀全镍(镀后冲)    ↑ 5G、150示意镀金5U\*或15U\*    ↑ 1G示意镀金1U\*    ↑ X公端    ↑ G母端    ↑ C示意90°    ↑ S示意180°

X普通  
L长  
S短  
U超薄

- SPECIFICATIONS
- Voltage rating: 250V AC/DC;
  - Current rating: 2.5A AC/DC;
  - Withstanding Voltage: 800V AC/minute
  - Insulation resistance: 1000MΩ Min
  - Temperature range: -25°C ~ +85°C
  - Contact resistance: 20mΩ Max
  - Applicable wire: AWG#22~#28
  - Relaxed requirements:
    - A. lax (0.08KG-0.2KG/PIN); B. taut (0.25KG-0.35KG)

东莞市羿通实业有限公司  
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

|  |  |  |  |                             |  |                   |  |                           |  |
|--|--|--|--|-----------------------------|--|-------------------|--|---------------------------|--|
|  |  |  |  | 料号PART NO: EST2504TBX-1GX-G |  |                   |  | 一般公差<br>GENERAL TOLERANCE |  |
|  |  |  |  | 品名 TITLE: 杜邦2.54-TC3        |  |                   |  | X.X ±0.25                 |  |
|  |  |  |  | 材料: C2680                   |  | 单位: MM            |  | X.XX ±0.20                |  |
|  |  |  |  | 日期版次<br>REVISION            |  | 日期<br>DATE        |  | X.XXX ±0.05               |  |
|  |  |  |  | 变更内容<br>DESCRIPTION         |  | 核 准<br>APPROVALBY |  | ANGLE ±1°                 |  |
|  |  |  |  | 日期: 2022/7/5                |  | 比例: 1:1           |  | ±1°                       |  |
|  |  |  |  | 制图: LI                      |  | 审核: LI            |  | 核 准: LI                   |  |
|  |  |  |  | 日期: 2022/7/5                |  | 日期: 2022/7/5      |  | 核 准: LI                   |  |