



**东莞市羿通实业有限公司**  
**DONGGUAN EASTOM ELECTRONIC Co., Ltd.**

PART NO: EST2512H-1\*3PX-X-X

TITLE: FUTAB0-3P Positive angle inner shell

Material: P466 UL94-V2

Unit: MM

Scale: 1:1

GENERAL	TOLERANCE
X, X	±0.25
X, XX	±0.20
ANGLE	±1°

**SPECIFICATIONS**

Applicable wire:AWG#22~#28  
 Voltage rating: 250V DC/AC (rms)  
 Current rating:3A max  
 Withstand voltage: 800V AC(rms)  
 Working Temperature:-25~+85  
 Lnsulation resistance: 1000M  
 Contact resistance: 0.02

日期版次	日期	变更内容	核 准
REVISION	DATE	DESCRIPTION	APPROVALBY

制图:	审核:	批准:	日期:
			2022.5.11

EST2512 H - 1\*NP X - B - X - HF-NK - X

- 羿通代码+间距
- X本色
- B黑色
- R红色
- L蓝色
- Y黄色
- G绿色
- C透明
- PNIN数
- 1示意单排
- 2示意双排
- H示意胶壳,
- H后无数字默认材质V0
- H后带数字2示意材质V2
- X公胶壳
- G母胶壳
- BF普通
- B带扣
- C侧胶
- 2L示高脚侧带推扣
- U超薄防呆型
- H带高凸点
- LC带低凸点
- K卡槽
- E有耳
- NE无耳
- HF示意无窗
- NF普通各窗
- NO MARK
- A灼热丝750
- B灼热丝850
- X普通料