



EST2512 H - 1*3P X - F - X - HF-NK - X

↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑

羿通代码+间距 H示意胶壳, H后无数字默认材质V0, H后带数字2示意材质V2

↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑

1示意单排, 2示意双排

↑ ↑ ↑ ↑ ↑

X普通, B带扣, C刺破, 2L示意两侧带锁扣, U超薄F防呆型, HV带高凸点, LC带低凸点, K卡槽, E有耳

X胶壳, G母胶壳

↑

NO MARK

↑

A灼热丝750, B灼热丝850, X普通料

↑

HF示意无齿, NF普通含齿

↑

↑

X本色, B黑色, R红色, L蓝色, Y黄色, G绿色, C透明

PIN数

SPECIFICATIONS:

VoItage rating: 250V AC, DC
 Current ratage: 3A AC, DC
 Withstanding Voltage: 1000v AC/minute
 Insulation resistance: 1000mΩ/min
 Temperature range: -25 C +85 C
 Contact resistance: Intial value/10m ° max
 After enviromental testing/20m ° max



东莞市羿通实业有限公司
 DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST2512H-1*3PB-F-X

品名 TITLE: FUTABO-3P斜内无耳

材料: PPO	单位: MM	包装规格: 1K/包	比例: 1:1
制图: LI	审核: LI	核准: LI	日期: 2022/07/12

一般公差
 GENERAL TOLERANCE
 X.X ±0.15
 X.XX ±0.05
 ANGLE ±1°

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

