



EST3001 T P X - 2 X - X

↑ 开通代码+间距 ↑ T示意端子 ↑ X普通脚 H高脚 E增高型脚 ↑ X普通 L长 S短 U超薄 ↑ X公端 G母端 C示意90° S示意180°

0素材 2镀锡先冲后镀 3镀锡先镀后冲 4镀全银(镀后冲) 4.2镀全银先冲后镀 5G、15G示意镀金5U"或15U" 16示意镀金1U"

SPECIFICATION

- Voltage rating: 250V DC/AC (rms)
- Current rating: 5A AC DC (rms)
- Withstand voltage: 1500V AC (rms)
- Working Temperature: -25°C + 85°C
- Insulation resistance: $\geq 1000M\Omega$
- Contact resistance: $\leq 0.01\Omega$
- Material: C5191



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST3001TPX-2X-X		一般公差 GENERAL TOLERANCE	
品名 TITLE: MX3.0-T公		X.X ±0.25	
材料: C5191	单位: MM	包装规格: 10K/卷	X.XX ±0.20
日期版次 REVISION	日期 DATE	制图:	比例: 1:1
		审核:	日期: 2020./07/30
变更内容 DESCRIPTION	核 准 APPROVALBY	核准:	审核:

ANGLE	±1°
-------	-----

