



EST1003 H - 1\*NP X - B - X - HF-NK - X

↑ 羿通代码+间距    ↑ PIN数    ↑ X公胶壳    ↑ NO MARK    ↑ A灼热丝750

X 本色    B 黑色    C 刺破    2L 示意两侧带锁扣    U 超薄防呆型    HV 带高凸点    LC 带低凸点    K 卡槽    E 有耳    NE 无耳    HF 示意无卤    NF 普通含卤

1 示意单排    2 示意双排

H 示意胶壳,    H 后无数字默认材质V0    H 后带数字2示意材质V2

B 灼热丝850    X 普通料

Poles	Dimensions (mm)	
	A	B
2x10	9.00	11.70
2x12	11.00	13.70
2x15	14.00	16.70
2x20	19.00	21.70
2x25	24.00	26.70

■ SPECIFICATIONS

- Voltage rating:50V AC/DC;
- Current rating:1A AC/DC;
- Withstanding Voltage:250V AC/minute
- Insulatin resistance:100MΩ Min
- Temperature range:-40℃~+85℃
- Contact resistance:20mΩ Max
- Material:PA66
- Wire Range:#28~#32
- Insulation O. D. :0.8mm(Max)



东莞市羿通实业有限公司  
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO:EST1003H-1\*NPX-B-X

品名 TITLE:1003-H带扣

材料: 单位: MM 包装规格: 比例: 1:1

制图: 审核: 核准: 日期: 2022. 3. 17

一般公差  
GENERAL TOLERANCE  
X.X ±0.30  
X.XX ±0.25  
ANGLE ±1°

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY