





EST1010 T P X - 2 X - X

↑ 异常代码+间距      ↑ T示意端子      ↑ X普通脚      ↑ X普通      ↑ X公端  
 ↑ G母端      ↑ H高脚      ↑ L长      ↑ S短      ↑ C示意90°  
 ↑ S示意180°

P磷铜  
 B黄铜  
 E合金铜

0基材  
 2镀锡先冲后镀  
 3镀锡先镀后冲  
 4镀全镀(镀后冲)  
 4.2镀全镀先冲后镀  
 56、156示意镀金5U"或15U", 16示意镀金1U"


- Specifications :
- Voltage rating: 50V AC / DC
  - Current rating: 1A AC / DC
  - Withstanding voltage: 250V AC/minute
  - Temperature range: -25°C~+85°C
  - Insulation resistance: ≥100MΩ
  - Contact resistance: ≤20mΩ
  - After environmental testing: ≤40mΩ



东莞市羿通实业有限公司  
 DONGGUAN EASTOM ELECTRONIC Co., Ltd.

TEL:13790510059  
 Address: 1/2 WORKSHOP BUILDING NO.53 LONGYAN NINTH ROAD ,HUMEI TOWN  
 DONGGUAN GUANGDONG CHINA

料号PART NO: EST1010TPX-2X-G		一般公差 GENERAL TOLERANCE	
品名 TITLE: 1004-T		X.X ±0.30	
材料: C5191		X.XX ±0.20	
日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY
单位: MM		包装规格:	比例: 1:1
核 准		核 准:	日期: 2022/02/22
制 图:		审 核:	
审 核:		核 准:	
审 核:		核 准:	



SL