



- 1、Applicable Wire Range: AWG#28~#32
- 2、Insulation O.D.: 0.80mm (Max.)
- 3、Current Rating: 2A AC,DC
- 4、Voltage Rating: 125V AC,DC
- 5、Temperature Rang: -25°C~+85°C
- 6、Contact Resistance: 20mΩ Max
- 7、Insulation Resistance: 100MΩ Min
- 8、Withstanding Voltage: 500V AC/minute

EST1250 H - 1\*NP X - K - X - HF-NK - X

羿通代码+间距      PIN数  
 1示意单排  
 2示意双排

X本色  
 B黑色  
 R红色  
 L蓝色  
 Y黄色  
 G绿色  
 C透明

X普通  
 B带扣  
 C刺破  
 L示意LOCK TYPE  
 U超薄F防呆型  
 HV带高凸点  
 LC带低凸点  
 K卡槽  
 E有耳  
 NE无耳

X公胶壳  
 G母胶壳

NO MARK

HF示意无卤  
 NF普通含卤

A灼热丝750  
 B灼热丝850  
 X普通料

Poles	Dimensions		
	A	B	
2	1.25	2.95	3.00
3	2.50	4.20	4.25
4	3.75	5.45	5.50
5	5.00	6.70	6.75
6	6.25	7.95	8.00
7	7.50	9.20	9.25
8	8.75	9.00	10.50
9	10.00	10.45	11.75
10	11.25	11.70	13.00
11	12.50	12.95	14.25
12	13.75	14.20	15.50
13	15.00	15.45	16.75
14	16.25	16.70	18.00
15	17.50	17.95	19.25
16	18.75	19.20	20.50

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY



## 东莞市羿通实业有限公司

### DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST1250H-1\*NPX-K-X

品名 TITLE: **MX1.25-H(有槽)**

材料: PA66 94-V0	单位: MM	包装规格: 1K/包	比例: 1:1
制图:	审核:	核准:	日期: 2022/04/03

一般公差  
GENERAL TOLERANCE

X.X ±0.30

X.XX ±0.25

X.XXX ±0.15

ANGLE ±5°

