

- NOTES:
1. Material:C5191
  2. Color:
  3. Corrent Roting:1A AC, DC
  4. Voltage rating:150V AC, DC
  5. Temperature Rang:-25° c~+85° c
  6. Conctoc Resistance:30mΩ Min
  7. Insulation Resistance:500MΩ Min
  8. Withstanding Voltage:500V AC/minute
  9. APPLICABLE WIRE:AWG#28~#32
  10. Q' TY:15000PCS/REEL

EST1252 T P X - 2 X - X

↑ 羿通代码+间距      ↑ T示意端子      ↑ P磷铜      ↑ 0素材

↑ X普通脚      ↑ H高脚      ↑ B黄铜      ↑ 2镀锡先冲后镀

↑ X普通      ↑ L长      ↑ E合金铜      ↑ 3镀锡先镀后冲

↑ S短      ↑ 4. 2镀全镍(镀后冲)

↑ X公端      ↑ G母端      ↑ C示意90°      ↑ S示意180°

↑ 5G、15G示意镀金5U"或15U", 1G示意镀金1U"

**EST** 东莞市羿通实业有限公司  
DGEASTOM DONGGUAN EASTOM ELECTRONIC Co., Ltd.


料号PART NO: EST1252TPX-2X-G

品名 TITLE: DF13-T

材料: 单位: MM 包装规格: 比例: 1:1

制图: 审核: 核准: 日期: 2021.11.30

一般公差  
GENERAL TOLERANCE  
X.X ±0.25  
X.XX ±0.20  
ANGLE ±1°



EST