



PART NO.	Dimensions	
	A	B
2X05P	5.00	12.50
2X07P	7.50	15.00
2X10P	11.25	18.75
2X15P	17.50	25.00
2X20P	23.75	31.25

EST1252 W VS - 2\*NP X - X X - X X - NK-HF

1单排 2双排  
 X本色 B黑色 R红色 L蓝色 Y黄色 G绿色  
 X普通 B带扣 U超薄 PH组合排针 FH组合排母 H高弯 P平弯  
 D防呆型 2示意有柱 3示意无柱  
 1为PPS, 2为PBT, 3为LCP, 4为ABS, 5为PA6T, 6为PA66  
 6为P-PIN针镀金 S为P-PIN针镀锡  
 NK为NO MARK 或为有MARK  
 排无孔 NP普通含孔  
 W示意针座 W后无0默认材质为V0 W后带2示意V2  
 V示意180°直针 VS立式 R示意90°弯针 RS卧式  
 界通代码-间距

- NOTES:
- Material: Nylon66, UL94V-0
  - Color:
  - Current Rating: 1A AC, DC
  - Voltage rating: 150V AC, DC
  - Temperature Range: -25° c ~ +85° c
  - Contact Resistance: 30mΩ Min
  - Insulation Resistance: 500MΩ Min
  - Withstanding Voltage: 500V AC/minute

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVAL BY



## 东莞市羿通实业有限公司

DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST1252WVS-2\*NPX-X-X

品名 TITLE: DF13-Wafer立式(双排)

材料:	单位: MM	包装规格:	比例: 1:1
制图:	审核:	核准:	日期: 2022.4.16

一般公差  
GENERAL TOLERANCE

X.X ±0.25

X.XX ±0.20

ANGLE ±1°


