



a-a section




b-b section



c-c section

技术参数: SPECIFICATIONS

- 适用线规: AWG#28~#32
Applicable wire: AWG#28~#32
- 额定电压: 250V DC/AC (有效值)
Voltage rating: 250V DC/AC (rms)
- 额定电流: 1.0A
Current rating: 1.0A
- 耐压值: 800V AC(有效值)
Withstand voltage: 800V AC(rms)
- 工作温度: -25℃~+85℃
Working Temperature: -25℃+85℃
- 绝缘电阻: ≥1000MΩ
Insulation resistance: ≥1000MΩ
- 接触电阻: ≤0.02Ω
Contact resistance: ≤0.02Ω



d-d section

EST1253 T P X - 2 X- X

↑ 羿通代码+间距
↑ T示意端子
↑ X普通
L长
S短
↑ X公端
G母端
0素材
2镀锡先冲后镀
3镀锡先镀后冲
5G、15G示意镀金5U"或15U", 1G示意镀金1U"
↑ X普通脚
H高脚
P磷铜
B黄铜
E合金铜

EST1253TPX-2X-X

		东莞市羿通实业有限公司 DONGGUAN EASTOM ELECTRONIC Co., Ltd.			一般公差 GENERAL TOLERANCE X.X ±0.15 X.XX ±0.05 ANGLE ±1°
		料号PART NO: EST1253TPX-2X-G 品名 TITLE: DF14- T			
材料: C5191	单位: MM	包装规格: 5K/卷	比例: 1:1	日期: 2022/04/16	
制图: LI	审核: LI	核准: LI	日期: 2022/04/16	EST	

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

6

5

4

3

2

1

EST