



技术参数: SPECIFICATIONS

- 适用线规: AWG#28~#32
Applicable wire: AWG#28~#32
- 额定电压: 250V DC/AC (有效值)
Voltage rating: 250V DC/AC (rms)
- 额定电流: 2.5-1.0A
Current rating: 2.5-1.0A
- 耐压值: 800V AC(有效值)
Withstand voltage: 800V AC(rms)
- 工作温度: -25℃~+85℃
Working Temperature: -25℃+85℃
- 绝缘电阻: ≥1000MΩ
Insulation resistance: ≥1000MΩ
- 接触电阻: ≤0.02Ω
Contact resistance: ≤0.02Ω

EST1254 T P X - 2 X - X

↑ 羿通代码+间距
↑ T示意端子
↑ X普通
↑ L长
↑ S短
↑ X公端
↑ G母端
↑ C示意90°
↑ S示意180°

0素材
2镀锡先冲后镀
3镀锡先镀后冲
5G、15G示意镀金5U"或15U", 1G示意镀金1U"

X普通脚
H高脚
P磷铜
B黄铜
E合金铜



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVAL BY	料号PART NO: EST1254TPX-2X-G				一般公差 GENERAL TOLERANCE	
A1	2021.1.12	分别将0.12更改为0.20, 0.75更改为0.80	胡宗显	品名 TITLE: FIS1.25 -T				X.X	±0.15
				材料: C5191	单位: MM	包装规格: 10K/卷	比例: 1:1	X.XX	±0.10
				制图:	审核:	核准:	日期: 2021/01/12	X.XXX	±0.05
								ANGLE	±1°

