

EST1256 T P X - 2 X - X

羿通代码+间距

T 示意端子


X 普通脚
H 高脚

X 普通
L 长
S 短
U 超薄


P 磷铜
B 黄铜
E 合金钢

0 素材
2 镀锡先冲后镀
3 镀锡先镀后冲
4 镀全银(镀后冲)
4.2 镀全银先冲后镀
5G、15G 示意镀金5U'或15U'
1G 示意镀金1U'


X 公端
G 母端
C 示意90°
S 示意180°



SEC:A-A



SEC:B-B



1.25mm Pitch wire to board connectors
 Voltage rating:50V AC/DC
 Current rating:1A AC/DC
 Withstandsing Voltage:500V AC/minute
 Insulation resistance:100M
 Temperature range:-25°C~+85°C
 Contact resistance:30mΩ Max
 Material:C5191
 Q'ty:1000PCS/Bag



东莞市羿通实业有限公司
 DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO:EST1256TPX-2X-G

品名 TITLE: GH1.25-T

材料: C5191

单位: MM

包装规格:

比例: 1:1

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

制图:

审核:

核准:

日期: 2022.2.12

一般公差 GENERAL TOLERANCE	
X.X	±0.30
X.XX	±0.25
X.XXX	±0.10
ANGLE	±1°

