



EST1502 H - 2*NP X - B - X - HF-NK - X

↑
羿通代码+间距

↑
PIN数

↑
X 本色
B 黑色
C 刺破

↑
X 公胶壳
G 母胶壳

↑
NO MARK

↑
A 灼热丝750
B 灼热丝850
X 普通料

1 示意单排
2 示意双排

X 普通
B 带扣
C 刺破
L 示意LOCK TYPE
U 超薄F防呆型
HV 带高凸点
LC 带低凸点
K 卡槽
E 有耳
NE 无耳

HF 示意无卤
NF 普通含卤

H 示意胶壳,
H 后无数字默认材质V0
H 后带数字2示意材质V2

SPECTION

- Current rating: 2A AC, DC (AWG #24)
- Voltage rating: 100V AC, DC
- Temperature range: -25°C to +85°C (including temperature rise in
- Contact resistance: Initial value/30mΩ max.After environmental testing /60mΩ max.
- Insulation resistance: 500M Ω min.
- Withstanding voltage: 500V AC/minute
- Applicable wire: Conductor size/AWG #28 to #24
- Insulation O. D. /0.8 to 1.2mm

Contacts	Dimensions(mm)			
	Dim A	Dim B	Dim C	Dim D
2x05	7.50	6.00	11.20	9.30
2x06	9.00	7.50	12.70	10.80
2x07	10.50	9.00	14.20	12.30
2x08	12.00	10.50	15.70	13.80
2x09	13.50	12.00	17.20	15.30
2x10	15.00	13.50	18.70	16.80
2x13	19.50	17.50	23.20	21.30
2x15	22.50	20.50	26.20	24.30



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST1502H-2*NPX-B-X

品名 TITLE: ZP1502-H

材料:

单位: MM

包装规格:

比例: 1:1

日期版次
REVISION

日期
DATE

变更内容
DESCRIPTION

核 准
APPROVALBY

制图:

审核:

核准:

日期:

2022. 4. 16

一般公差
GENERAL TOLERANCE
X. X ±0.30
X. XX ±0.20
ANGLE ±1°

