



EST1500 T B X - 2 X - X

↑ 羿通代码+间距 ↑ T 示意端子 ↑ P 磷铜 ↑ B 黄铜 ↑ E 合金铜

↑ X 普通脚 ↑ H 高脚 ↑ 0 素材 ↑ 2 镀锡先冲后镀 ↑ 3 镀锡先镀后冲 ↑ 5G、15G 示意镀金5U"或15U", 1G 镀金1U"

↑ X 普通 ↑ L 长 ↑ S 短 ↑ X 公 ↑ G 母 ↑ C 示意90° ↑ S 示意180°

PRODUCT SPECIFICATON

1. SURFACE TREATEMENT: Tin plated brass terminal
2. Temperature range: -25°C ~ 85°C
3. Current rating: 0.7A AC/DC
4. Contact resistance: 20mΩ MAX
5. Insulation resistance: 1000MΩ MIN
6. Withstand voltage: 1000V AC/Minute
7. Applicable wire: #24~28

东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

				料号PART NO: EST1500TBX-2X-S				一般公差 GENERAL TOLERANCE	
				品名 TITLE: SZN1.5-T (180°)				X.X ±0.30	
				材料:C2680		单位: MM		X.XX ±0.20	
				日期版次 REVISION		日期 DATE		ANGLE ±1°	
				变更内容 DESCRIPTION		核 准 APPROVALBY		制图: 审核: 批准: 日期:	
				日期版次 REVISION		日期 DATE		制图: 审核: 批准: 日期:	