

SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 650V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Black


A2005 H - NP - N0 BK

① ② ③ ④ ⑤

- ① Series No.
- ② Category: H-Housing
- ③ Circuit No.: 02-2PIN~15-15PIN
- ④ Material: N0-Nylon66, UL94V-0
- ⑤ Color: BK-Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2005H-02P	2.00	6.00
A2005H-03P	4.00	8.00
A2005H-04P	6.00	10.00
A2005H-05P	8.00	12.00
A2005H-06P	10.00	14.00
A2005H-07P	12.00	16.00
A2005H-08P	14.00	18.00
A2005H-09P	16.00	20.00
A2005H-10P	18.00	22.00
A2005H-11P	20.00	24.00
A2005H-12P	22.00	26.00
A2005H-13P	24.00	28.00
A2005H-14P	26.00	30.00
A2005H-15P	28.00	32.00

日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更内容 DESCRIPTION	审核 CHK	核准 APPD	角法 PROJECT	一般公差 GENERAL TOLERANCE	 东莞汉钛电子有限公司 HINGTAK PRODUCT INC.	料号 PART NO	A2005H-NP-N0BK
						.X ±0.3 .XX ±0.2 .XXX ±0.1	核准 APPD 审核 CHK 绘图 DR 日期 DATA		单位 UNIT MM 比例 SCALE 1/1 图号 NUMBER LDZY-8801 版次 REV A	